






SYMBOLS

-  Work area
-  Cone, drum or barricade (not required for moving operations)
-  Sign on portable or permanent support
-  Flagger with traffic control sign
-  Barricade or drum with flashing light

GENERAL NOTES

* Cones at 8 m (25') centers for 75 m (250'). Additional cones may be placed at 15 m (50') centers. When drums or Type I or Type II barricades are used, the interval between devices may be doubled.

Where, at anytime, day or night, any vehicle, equipment, workers or their activities encroach on the pavement requiring the closure of one traffic lane in an area where the posted speed limit is 70 km/h (40 mph) or less.

If the work operation is performed between 9:00 am and 3:00 pm and does not exceed 15 minutes, traffic protection shall be as shown for Standard 701301. Signs, when required, shall be installed at 60 m, (200') spacing.

Form BT 725 is required.

All dimensions are in millimeters (inches) unless otherwise shown.

Illinois Department of Transportation	
APPROVED <i>[Signature]</i> January 1, 1998 ENGINEER OF OPERATIONS	ISSUED 1-1-97
APPROVED <i>[Signature]</i> January 1, 1998 ENGINEER OF DESIGN AND ENVIRONMENT	

DATE	REVISIONS
1-1-98	Added 48" dimension to W sign designations.
1-1-97	Renum. Standard 2401.
	Del. orange flags. Rev. note for cone symbol.

LANE CLOSURE 2L, 2W
UNDIVIDED
FOR SPEEDS < 45 MPH

STANDARD 701501-01